



**RIPE
NCC**

WEIRDS @ RIPE

Ed Shryane

Database Group, RIPE NCC

- Limited data model
 - RPSL (Routing Policy Specification Language) (RFC 2622) is essentially free-form text.
- Not internationalised
 - Originally US-ASCII, RIPE Whois is latin-1 (ISO-8859-1)
- No Authentication
 - Not possible to do authenticated queries
- No redirection
 - canonical datasources (other RIRs) are mirrored
 - no bootstrapping
- Command-line oriented (port 43)

- Alternative to Whois
- Lookup Only (updates are not supported)
- Names and Numbers
 - RIRs: numbers (resources)
 - TLD: names
- Uses Standard Transport and Data Protocols

- WEIRDS - The Service
 - “Web Extensible Registration Data Service”
- RDAP - The Protocol
 - “Registration Data Access Protocol”
- IETF Working Group
 - <http://datatracker.ietf.org/wg/weirds/>
 - Formed in April 2012

- Builds on Existing Standards
 - Uses HTTP as transport protocol
 - Query parameters in URL
 - Standard Status Codes in Response
 - Support for transport security
 - Support for authentication
 - Supports redirection
 - RDAP Uses RESTful URI scheme
 - Uses JSON as data format
 - Structured format, well understood
 - Easy for Developers to work with

- **aut-num**
- **IP (inetnum, inet6num)**
- **Entity (organisation, person, role)**
- **Nameserver**
 - Not implemented by RIPE NCC
- **Domain**
 - Only reverse domains in RIPE Database

- Beta deployment since July 2013
 - <https://rdap.db.ripe.net/>
- Live data (up to date)
- Java, open source
 - <https://github.com/RIPE-NCC/whois>
- Participated in IETF WG Interop Testing
- Collaboration with APNIC on implementation

```
inetnum:      193.0.0.0 - 193.0.7.255
netname:      RIPE-NCC
descr:        RIPE Network Coordination Centre
org:          ORG-RIEN1-RIPE
descr:        Amsterdam, Netherlands
remarks:      Used for RIPE NCC infrastructure.
country:      NL
admin-c:      JDR-RIPE
admin-c:      BRD-RIPE
tech-c:       OPS4-RIPE
status:       ASSIGNED PI
source:       RIPE # Filtered
mnt-by:       RIPE-NCC-MNT
mnt-lower:    RIPE-NCC-MNT
```

```
{ "handle" : "193.0.0.0 - 193.0.7.255",
  "startAddress" : "193.0.0.0/32",
  "endAddress" : "193.0.7.255/32",
  "ipVersion" : "v4", "name" : "RIPE-NCC",
  "type" : "ASSIGNED PI",
  "country" : "NL",
  "entities" : [ {
    "handle" : "OPS4-RIPE",
    "vcardArray" : [ ],
    "roles" : [ "abuse" ],
    "entities" : [ ] } ],
  "remarks" : [ {"description" : [ "RIPE Network Coordination Centre", "Amsterdam, Netherlands" ]} ],
  "links" : [ ],
  "events" : [ {"eventAction" : "last changed", "eventDate" : "2013-03-19T16:24:19Z"} ],
  "rdapConformance" : [ "rdap_level_0" ],
  "notices" : [ {"title" : "Filtered", "description" : [ "This output has been filtered." ]},
    {"title" : "Source", "description" : [ "Objects returned came from source", "RIPE" ]},
    {"title" : "Terms and Conditions",
      "description" : [ "This is the RIPE Database query service. The objects are in RDAP format." ],
      "links" : [ ]} ],
  "port43" : "whois.ripe.net" }
```

- Bootstrap*
- JSON Response
- Object Inventory
- RDAP Query*
- RDAP Security (DONE)
- Redirects
- Using HTTP (DONE)

